For Mercedes-benz A CLASS 2013-2015
Installation Guide

1. Original Monitor (Please power off before installation)

2.Pry out the right and left conditioning vent

3.Loosen the original car fixing screws

4.Remove the power harness from original host, and connect it to android harness.

5.Connect android USB cable to USB jack in Original armrest box. (Note: ,this step can be omitted if car is NTG5.0/2016year)

6.Pry the screws cover of the monitor out and remove screws

7.Pry decorative frame out from the stand of original monitor

8. Take out the fixed stand of original monitor

9. Put cables well,and assemble back stand of original monitor

10.Fixing the android monitor well, and lock the screws.

11.Effect picture after installation

12. Android Cables connector

1.4G antenna Port
2.GPS antenna Port
3.RCA cable LVDS adapter
4.RCA Port
5.USB Port
6.Android Power Interface
7.2015/2016year shared CAN interface
8.2015/2016year short-circuited wiring interface
9.Audio USB port
10.2015year CAN interface
11.2016year CAN interface
12.ISO female plug
13.ISO male plug

For CLA 2013-2018
Installation Guide

1. Original Monitor (Please power off before installation)

2.Pry the cover of the monitor screws out and remove screws

3.Pry decorative frame out from the stand of original monitor

4. Pry out the rightmost conditioning vent

5. Take out the fixing screws of air conditioning port

6. Pry the air conditioning vent panel

7. Take out the fixed stand of original monitor

8. Loosen the original car fixing screw

9.Remove the power harness from original host,and connect it to android harness.

10. Put cables well,and assemble back stand of original monitor

11.Fixing the android monitor well, and lock the screws.

12.Effect picture after installation

13. Android Cables connector

1.4G antenna Port
2.GPS antenna Port
3.RCA cable LVDS adapter
4.RCA Port
5.USB Port
6.Android Power Interface
7.2015/2016year shared CAN interface
8.2015/2016year short-circuited wiring interface
9.Audio USB port
10.2015year CAN interface
11.2016year CAN interface
12.ISO female plug
13.ISO male plug